

## FMOC-DL-Lysine-(boc)-OH on Lux 5 µm Cellulose-2 250 x 4.6mm in NP

**Column:** Lux® 5 µm Cellulose-2, LC Column 250 x 4.6 mm, Ea

**Dimensions:** 250 x 4.6 mm ID

**Order No:** 00G-4457-E0

**Elution Type:** Isocratic

**Eluent A:** 0.1% TFA in Hexane

**Eluent B:** 0.1% TFA in IPA

| Gradient Profile: | Step No. | Time (min) | Pct A | Pct B |
|-------------------|----------|------------|-------|-------|
| 1                 | 1        | 20         | 85    | 15    |

**Flow Rate:** 1 mL/min

**Col. Temp.:** ambient

**Detection:** Refractive Index @ 0.0000000000 (ambient)

**Analyst Note:** SecurityGuard™ Guard Cartridge System extends column lifetime.

- SecurityGuard Cartridges, Lux Cellulose-2, 4 x 3.0mm ID, 10/Pk Part No.: AJ0-8366


- Holder Part No.: KJ0-4282



Products used in this application:



18734



### ANALYTES:

**1** FMOC-Lys(Boc)-OH

Retention Time: 12.5 min

**2** FMOC-Lys(Boc)-OH

Retention Time: 16.1 min

